



24/08/2023 Revision 1

# **Clear Grease**

# **PRODUCT OVERVIEW**

Clear Grease is easy to apply, has high load capability and operates across a wide range of temperatures.

Continued lubrication helps to reduce friction, repel moisture and extend component life.

Colourless formulation is ideal for all applications & locations.

#### **FEATURES AND BENEFITS**

- A high quality clear grease
- Provides a water-resistant lubricant and protective film
- Easy in-situ greasing of bearings, pivots, couplings, linkages, and other moving parts
- Easy to apply

#### TYPICAL APPLICATIONS

Recommended for automotive, industrial, rail and marine applications

#### **DIRECTIONS FOR USE**

**Directions:** Shake can well before use. Spray from 20 - 25cms onto parts to be lubricated. Wipe off any overspray with a soft lint free cloth.

# **TECHNICAL DATA**

**APPEARANCE** Colourless Paraffinic **ODOUR** VOC Content: 68.8% >230°C **AUTO-IGNITION TEMP** 

FLAMMABILITY Extremely Flammable

70 PSI (at 25°c) **PRESSURE** 

### PACKAGING SPECIFICATIONS

PRODUCT NUMBER **SPA1023 UNIT SIZE** 500ml **CASE SIZE** 12

Bar Code 0793591223339

UFI: STT2-3OSM-6OOK-SKDU Store below 50°c, avoid direct **STORAGE** 

sunlight



**Emissco Products Ltd, Brookhouses Industrial Estate New Haden Road Cheadle** Staffordshire ST10 1UF Tel: +44 (0) 1538 752561

Email: info@emissco.co.uk