

Emissco

Silicone Spray Aerosol

Technical Data Sheet



Silicone Spray

PRODUCT OVERVIEW

Silicone Spray is designed to lubricate plastic, wood, rubber, nylon and metal & prevent the jamming & freezing of sliding doors and windows. Silicone Spray creates a frictionless clean invisible coating on all sliding surfaces, it also is highly effective at protecting against rust and corrosion.

FEATURES AND BENEFITS

- Prevents jamming
- Waterproofs and protects
- Eases all sliding surfaces
- Protect against rust and corrosion

TYPICAL APPLICATIONS

For general purpose uses on metals, plastics and most other hard, impervious surfaces, particularly within the automotive trade for the lubrication of locks, hinges, door seals, window channels, aerials, battery terminals, "squeak and creak" locations

DIRECTIONS FOR USE

Directions: Shake can well before use. Spray a light coating onto affected areas from 20-30 cms, 8 - 10 inches in even strokes.

Wipe away excess with a lint free cloth.

Warning. do not use near surfaces to be painted, glued or bonded.

TECHNICAL DATA

APPEARANCE	Colourless
ODOUR	Paraffinic
VOC	Content: 86.8%
AUTO-IGNITION TEMP	>230°C
FLAMMABILITY	Extremely Flammable
PRESSURE	70 PSI (at 25°C)

PACKAGING SPECIFICATIONS

PRODUCT NUMBER	SPA1015
UNIT SIZE	500ml
CASE SIZE	12
Bar Code	0793591223148
UFI:	E4T2-M07A-A00C-TH14
STORAGE	Store below 50°C, avoid direct sunlight



**Emissco Products Ltd,
Brookhouses Industrial Estate
New Haden Road Cheadle
Staffordshire ST10 1UF
Tel: +44 (0) 1538 752561**

Email: info@emissco.co.uk