

Emissco

White Grease Aerosol

Technical Data Sheet



White Grease

PRODUCT OVERVIEW

A scientifically prepared grease formulated to resist heat & water and also protect against corrosion. White Grease can be used on door and boot hinges, most linkages in the engine bay, 'O' rings, gears, bearings, springs, sliding shackles & striker plates. Lubricates all hard surfaces, such as plastic, steel & aluminium

FEATURES AND BENEFITS

- Lubricates and protects all moving parts
- Resists heat & moisture
- Short term corrosion protection
- Frees seized brakes
- For use in the auto & industrial sectors

TYPICAL APPLICATIONS

For general purpose low to medium temperature lubrication applications, particularly in the automotive, marine & industrial sectors, and especially in wet and humid environments. It is suitable for use on all types of threaded components, flanges, anti-friction and plain bearings, gears, cogs.

DIRECTIONS FOR USE

Directions: Shake can well before use. Spray from 20 - 25 cms, 8 - 10 inches onto area to be lubricated, use extension to access hard to reach areas. Avoid overspray on belts, hand & foot controls. Remove any excess with a clean lint free cloth.

Not for use in contact with food.

TECHNICAL DATA

APPEARANCE	White/off white
ODOUR	Paraffinic
VOC	Content: 77%
AUTO-IGNITION TEMP	>230°C
FLAMMABILITY	Extremely Flammable
PRESSURE	70 PSI (at 25°C)

PACKAGING SPECIFICATIONS

PRODUCT NUMBER	SPA1009
UNIT SIZE	500ml
CASE SIZE	12
Bar Code	0793591223070
UFI:	HMS2-K02X-G00D-UFHR
STORAGE	Store below 50°C, avoid direct sunlight



**Emissco Products Ltd,
Brookhouses Industrial Estate
New Haden Road Cheadle
Staffordshire ST10 1UF
Tel: +44 (0) 1538 752561**

Email: info@emissco.co.uk